

CP1 PRISMATIC SCOPE



SIG SAUER[®]
when it counts™

OWNER'S MANUAL

CP1 PRISMATIC SCOPE

The CP1 Prismatic Scope is a lightweight solution for fast target acquisition. This rugged and reliable scope provides assured accuracy from a 3X fixed magnification reticle, graduated to 600 meters. It features three reticle modes – non-illuminated black, illuminated green and illuminated red, with each illuminated mode offering 5 brightness settings. Anodized aluminum construction ensures optimal performance in the most extreme conditions.

CONTENTS

1. CP1 Prismatic Scope 2. Owner's Manual 3. 3V CR2032 Lithium Battery

FEATURES

- 3 reticle modes – non-illuminated black, illuminated green and red.
- 5 brightness settings for each illuminated mode (green and red)
- 3X fixed magnification ranging reticle
- Windage & elevation adjustments
- Anti-reflect & multilayer band pass optical coating
- M1913/Weaver rail mount

CP1 PRISMATIC SCOPE



INSTRUCTIONS

- Unscrew battery cover, using coin, then thumb/forefinger
- Position battery + facing out
- Reattach battery cover, tighten completely to o-ring

To mount on M1913/Weaver accessory rail:

- Loosen locking bolt using coin or screwdriver
- Mount on rail, and secure by tightening locking bolt
- CP1 is in non-illuminated mode, with the rotary switch set to 0. Switch to illuminated green or red brightness settings 1 – 5 by rotating switch left or right. Settings are colored green or red to correspond with reticle pattern color.
- Adjust windage and elevation by removing turret covers and using coin or screwdriver – counterclockwise: move impact left/up – clockwise: move impact right/down.
1 click = 1/4" @ 100 yds. Secure covers once set.

CP1 PRISMATIC SCOPE

Reticle type	Reflective prism ranging reticle
Reticle color	Illuminated red, green or non-illuminated black
Magnification	3X
Eye Relief	5.9" / 82mm
Exit Pupil	.4" / 10.6mm
Parallax setting	100 yds
Optical coating	Anti-reflect & multilayer band pass
Power/Obj. lens	1.3" / 32mm
Field of view	6 degrees, 10.5m@100m
Adjustment range	2 degrees
Windage/elevation	1/4"@100 yds
Mounting	M1913 / Weaver
Temp range	-5 degrees F to +130 degrees F
Water resistance	0.5m for 20 minutes
Length/diameter	5.8" x 1.2" (146mm x 30mm)
Weight	13.9 oz / 390g

BATTERY HAZARD WARNING

Battery manufacturers warn against mixing new and used batteries or different brand batteries together as this may increase the risk of leakage, fire or explosion. Do not, puncture, short-circuit, disassemble or heat batteries above 212°F (100°C). Do not recharge the batteries unless they are specifically designed as rechargeable batteries and then only in accordance with manufacturer's directions.

Lithium Batteries: Industry wide there have been reported incidents of off-brand Lithium batteries exploding or catching fire creating serious consequences. Sig Sauer, Inc. includes batteries from Duracell® and other well-known battery manufacturers with its products, and strongly urges you to only purchase replacement batteries from Duracell®, or other well-known battery manufacturers like Panasonic® and Rayovac®. These batteries are designed for use in high performance, high-drain devices, and their designs incorporate fault and heat protection for added safety. Use of inferior batteries may cause an explosion or fire, creating risk of damage to your device that will void the SIG Sauer Inc. warranty, cause damage to other property, and potentially serious injury or death.

STATEMENT OF LIABILITY

This device is classified as a FIREARMS ACCESSORY and is sold by us with the specific understanding that we are not responsible in any manner whatsoever for its safe handling or resale under local laws and regulations. SIG SAUER Inc. shall not be responsible in any manner whatsoever for malfunctioning of the firearm, for physical injury or for property damage resulting in whole or in part from (1) criminal or negligent discharge, (2) improper or careless handling, (3) unauthorized modifications, (4) defective, improper, hand-loaded, or reloaded ammunition, (5) corrosion, (6) neglect, or (7) other influences beyond our direct and immediate control. This limitation applies regardless of whether liability is asserted on the basis of contract, negligence or strict liability (including any failure to warn). Under no circumstances shall SIG SAUER Inc. be liable for incidental or consequential damages, such as loss of use of property, commercial loss and loss of earnings or profits.

SIG SAUER® LIMITED ONE YEAR WARRANTY

SIG SAUER® warrants that the enclosed accessory was originally manufactured free of defects in material, workmanship and mechanical function, and agrees to correct these defects by repair, adjustment or replacement, at the option of SIG SAUER, with items of the same or comparable quality; provided, however, that the accessory is returned freight prepaid to SIG SAUER at 18 Industrial Drive, Exeter, NH 03833 by the original purchaser within one year of the date of purchase.

This limited warranty is null and void if the accessory has been misused, damaged (by accident or otherwise), or if unauthorized repair or any alteration, including of a cosmetic nature, has been performed on the accessory. This limited warranty does not apply to normal wear and tear of any parts.

Subject to the foregoing, this limited warranty confers the right to have the covered accessory or its parts repaired, adjusted or replaced exclusively by the original purchaser, which right is not transferable to any other person. NO IMPLIED WARRANTIES OF ANY KIND, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE MADE HEREIN, and this warranty does not apply to any accessory items attached or appurtenant to this accessory. In no event shall SIG SAUER be liable for incidental or consequential damages arising from or in connection with this limited warranty.