





## SIG V-CROWN™ 380 AUTO - 90GR

380 AUTO	BARE GELATIN				HEAVY CLOTHING				PLYWOOD				DRYWALL				AUTO GLASS				STEEL			
	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)
<b>SIG V-CROWN 380 AUTO 90gr E380A1</b> 	895	8.1	0.556	90	895	15.4	0.408	90	918	12.0	0.429	90	902	10.5	0.455	90	884	6.6	0.464	61	922	9.5	0.414	90
	<b>A</b> 	983	7.9	0.534	90	992	9.1	0.499	89	993	14.1	0.391	90	1000	9.6	0.485	90	955	6.1	0.544	71	987	9.7	0.459
<b>B</b> 		944	8.1	0.546	90	944	11.3	0.454	90	959	13.25	0.405	90	956	14.2	0.412	90	951	5.25	0.474	57	962	10.3	0.428
	<b>C</b> 	910	8.4	0.482	89	912	9.2	0.756	89	929	10.2	0.445	89	934	8.5	0.492	89	908	4.5	0.459	51	933	*	0.571

Note: Test data shot from SIG P328 (2.8" BBL).

\*No gelatin penetration