





SIG V-CROWN™ 40S&W 180gr - INTERNAL FBI TESTING

40S&W	FBI SCORE	BARE GELATIN				HEAVY CLOTHING				PLYWOOD				DRYWALL				AUTO GLASS				STEEL			
		Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)	Velocity (ft/sec)	Penetration (in)	Expansion (in)	Retained Weight (gr)
SIG V-CROWN 180gr JHP E40SW2	358																								
		1038	13.4	0.662	178	1039	16.2	0.587	180	1027	15.0	0.590	180	1030	14.9	0.587	180	1038	14.1	0.497	126	1031	19.7	0.477	180
A	358																								
		992	13.7	0.591	179	984	13.6	0.567	179	983	14.7	0.579	178	994	12.7	0.581	179	985	11.6	0.672	155	994	18.6	0.484	178
B	316																								
		902	12.4	0.604	179	915	14.2	0.589	180	905	14.8	0.514	179	933	13.3	0.588	179	911	11.3	0.633	169	921	19.4	0.468	180
C	333																								
		1013	12.4	0.651	180	1030	13.3	0.646	180	1017	18.5	0.472	163	992	13.0	0.608	180	1016	13.5	0.523	125	1016	18.7	0.483	179

Note: Testing is per Department of Justice Federal Bureau of Investigation Request for Proposal RFP-OSCU-TD2WP7101, November 15, 2011.